



# Canopy

Ideal replacement for traditional HID luminaires.

SYLVANIA Canopy luminaires are energy saving, environmentally preferable LED alternatives to traditional HID luminaires and are offered in two wattages and lumen packages with 4000K and 5000K color temperature options and luminous efficacy up to 117 LPW. All luminaires are 0-10V dimmable down to 12%. The luminaires are constructed with one-piece cast aluminum alloy housing with powder coated paint finish and acrylic (PMMA) lens delivering a Type V distribution. They come with a 5-year warranty.

### Recommended applications

- Canopy and entryway
- Parking garages
- Stairwells



### Product overview

- Extremely durable, low profile luminaire (<2.7")
- Hanging cable included for hands free wiring allowing for easy surface or pendant installations
- Energy savings of up to 78%
- Controls ready with 0-10V dimming for additional energy savings
- Rated life  $\geq 125,000$  hours ( $L_{70}$ )
- Instant on/instant restrike
- Wet location rated
- Wide operating temperature range -40°F to +104°F



\*For more details about which products are DLC Standard or DLC Premium, please visit pages 34-37.





### Savings in energy and costs over the LED lifetime per fixture\*\* LED vs. Traditional

	Energy consumption	Costs
Metal Halide 175W equivalent - 210W	26,250 kWh	\$3,556
SYLVANIA LED Canopy - 55W	6,875 kWh	\$756
<b>SAVINGS</b>	<b>74%</b>	<b>\$2,800</b>

\*\*Energy costs based on \$0.11/kWh.

Traditional costs include energy cost, cost to replace lamps and ballast over the LED product life. LED cost does not include cost of the luminaire.

**Canopy**



**Ordering Information (120-277V)**

Item Number	Product Description	Power (W)	Input Voltage	Dimming	Replacement for up to	Total Fixture Lumens	LPW*	Rated Life L <sub>70</sub> (hours)	CCT	CRI	Distribution
74171	Canopy UNV 40W 4000K	40W	120-277	0-10V	150W MH/HPS	4800	115	≥125,000	4000K	>70	Type V
74173	Canopy UNV 40W 5000K	40W	120-277	0-10V	150W MH/HPS	4900	117	≥125,000	5000K	>70	Type V
74172	Canopy UNV 55W 4000K	55W	120-277	0-10V	150W MH/HPS	6000	105	≥125,000	4000K	>70	Type V
74174	Canopy UNV 55W 5000K	55W	120-277	0-10V	150W MH/HPS	6200	108	≥125,000	5000K	>70	Type V

\*LPW per LM79 Report

**Ordering Information (347V)**

Item Number	Product Description	Power (W)	Input Voltage	Dimming	Replacement for up to	Total Fixture Lumens	LPW*	Rated Life L <sub>70</sub> (hours)	CCT	CRI	Distribution
74273	Canopy 347V 45W 4000K	45W	347	0-10V	150W MH/HPS	4800	100	≥125,000	4000K	>70	Type V
74275	Canopy 347V 45W 5000K	45W	347	0-10V	150W MH/HPS	4900	102	≥125,000	5000K	>70	Type V
74274	Canopy 347V 60W 4000K	60W	347	0-10V	150W MH/HPS	6000	95	≥125,000	4000K	>70	Type V
74276	Canopy 347V 60W 5000K	60W	347	0-10V	150W MH/HPS	6200	98	≥125,000	5000K	>70	Type V

\*LPW per LM79 Report

**Accessories and Replacement Parts**

Item Number	Product Description
74446	12.5" Mounting Plate, White Finish
74447	16" Mounting Plate, White Finish

